

TECHNICAL DATA

TAMPER

BVT 65



Reliable and long lasting

Engine protection, fuel filter, automatic oil level control



More transparency

Hour meter RPM-meter with service indicator (optional)




Simple operation

Engine and fuel supply with combined switch

Shipping dimensions in cub.yd

BVT 65 0.345



Standard Equipment

- Engine Protection System
 - Protective engine covering
 - Automatic oil level control
 - Dual fuel filter system
- Vibration insulated steering bow
- Self-cleaning air filter housing
- Protective covering
- Single point lifting device
- Recoil starter
- Plastic castor as loading aid
- Infinitely variable frequency
- Combination of engine stop/fuel switch
- 3-2-1 Warranty

Optional Equipment

- Transport device with puncture proof wheels
- Tamper foot widths (6.3-13in)
- Tamper foot extensions
- h-/ rpm meter
- Special painting
- Tool kit
- Service Kit
- TOUGH WARRANTY

Dimensions in in

	B	H	L	L1	W
BVT 65	13.8	40.6	28.7	13.2	11.0

Technical Data

**BOMAG
BVT 65**

Weights

Operating weight CECE	lb	148
Basic weight	lb	146

Dimensions

Working width (tamper plate)	in	11.0
------------------------------------	----	------

Driving Characteristics

Working speed max.	ft/min	65.6
Area coverage max.	ft ² /h	3,616.8

Drive

Engine manufacturer	Honda
Type	GX 100
Emission stage	CARB Phase III
Cooling	air
Number of cylinders	1
Performance SAE J 1349	hp 3.1
Fuel	gasoline
Drive system	mech.
Fuel comsump. aver. during operation	gal/h 0.2

Exciter system

Frequency	vpm	600- 708
Impact force	lb	3,597

Capacities

Fuel	gal	0.8
------------	-----	-----

Technical modifications reserved. Machines may be shown with options.



PRUS 541 21 010

190916 Sa

BOMAG Americas, Inc.
 125 Blue Granite Parkway
 Ridgeway, SC 29130
 USA
 Tel. +1 803 3370700
 Fax +1 803 3370800
 www.bomag.com/us

